

# black AIR-board® ECO PC clear






### PRODUCT DESCRIPTION

black AIR-board® ECO PC clear honeycomb panels are made with two polycarbonate (PC) core options and clear PC facing sheets with sustainable raw material content. PC ECO is the facing layers and has a biocircular material content and low CO2 footprint.

Normally manufactured using fossil fuels, these components have been replaced by bio-based renewable raw materials. The attributed share is up to 83% of the total material content. In addition, black AIR-board ECO PC clear is 100% recyclable. These lightweight panels combined with two different core options can be used in many different ways in interior architecture to suit the needs of your design.



#### **COLOR**

Clear facings with black honeycomb core.

## **CORE**

black AIR-board® ECO PC cell diameter 7 mm/0.27" chaos black AIR-board® ECO PC cell diameter 4/7/12 mm - 0.15" / 0.27" / 0.47"

## **DIMENSIONS**

FORMAT	LENCTH [MM/INCHES]	WIDTH [MM/INCHES]	**THICKNESS [MM/INCHES]		
Standard	3,020/118.8	1,220/48	19/0.75		
Special Dimensions*					
black AIR-board® ECO PC clear chaos black AIR-board® ECO PC clear	max. 3,500/137 max. 3,020/118.8	max. 1,500/59 max. 1,300/51	max. 30/1.18 max. 30/1.18		
Production/Cutting Tolerance	2/-2 to 0.08/-0.08	1/-2 to 0.04/-0.08	0/-1 to 0/-0.04		

<sup>\*</sup>On request – minimum orders apply

# PHYSICAL PROPERTIES

COEFFICIENT OF THERMAL EXPANSION ACC. TO DIN 537522-A [1/K]	SERVICE TEMPERATURE [C/F]	FACING SHEETS	* ESTIMATED LIGHT TRANSMISSION [%]
6 x 10 <sup>-5</sup>	-30 to +80 / -22 to 176	2mm PC clear	-

<sup>\*</sup>estimated using standard thickness of 19 mm / 3/4"









<sup>\*\*</sup> Thickness of 12mm/0.47", 16mm/0.63" and 30mm/1.18" are also available, minimums or extended lead times may apply



# black AIR-board® ECO PC clear





### **MECHANICAL PROPERTIES**

THICKNESS [MM/INCHES]	WEIGHT PER UNIT AREA [KG/M²/LBS/SQFT]	THERMAL INSULATION U-VALUE [W/M²K]	SOUND INSULATION RW [DB]	*MODULUS OF ELASTICITY [N/MM²]
19/0.75	5.9/1.20	2.4	21	532
30/1.18	6.6/1.35	1.7	23	1,688

<sup>\*</sup>per 1m panel width

## FIRE CLASSIFICATION

FIRE CLASSIFICATION	ASTM D-2843	ASTM D-635	ASTM D-1929
	SMOKE DENSITY [%]	BURNING RATE [INCHES]	SELF IGNITION TEMP. [F]
C1/CC1	36.50%	0.47"	1,095

### POPULAR APPLICATIONS







## **INFINITE POSSIBILITIES**

Moxie Surfaces is the US Distributor of Design Composite. We specialize in creative finishing materials with infinite possibilities. Our unique architectural elements stimulate the senses and help create beautiful environments for learning, living, and enjoying our lives.

Our products provide a variety of benefits including sound absorption, light transmission and thermal insulation, while offering unlimited applications for indoor or outdoor design.

## **NOTES**

All information and specifications contained herein are based on the most up-to-date information available and to the best of our knowledge. These specifications are subject to change at any time. A legally binding assurance of certain properties or the suitability of an individual type for a specific field or application cannot be inferred from these specifications. All information is provided without any obligation. No legal liability can or will be assumed.







